

ATHLETIC & RECREATIONAL SURFACES: 02790

FOUR (4) PART SPECIFICATIONS:

1.) Product:

Resilient, rubberized safety surfacing flooring and paver products in the tile/mat/block form.

2.) Manufacturing Plant:

Unity Creations, LTD.
3997 RT 9W (PO Box 9)
Saugerties, NY. 12477
T: (845) 246-2700
F: (845) 246-1700
E-mail: techinfo@surfacingystems.com
Internet: www.surfacingystems.com

Sales & Marketing Dept:

Unity Creations, LTD
3997 RT 9W (PO Box 9)
Saugerties, NY. 12477
T: (845) 246-2700
F: (845) 246-1700
E: productinfo@surfacingystems.com
Internet: www.surfacingystems.com

PART ONE (1) GENERAL:

1.01 SUMMARY

A.) Section Includes:

Rubberized safety surfacing, flooring and pavers, in the tile/mat/block form.

B.) Related Sections:

Division 2 Sitework Sections: Materials and Methods, Excavation, Asphalt Paving, Concrete Paving, Sub-Drainage, Storm Drainage, Fencing, Playground Equipment, Rooftops and Structures.

1.02 REFERENCES

A.) American Standard for Testing Materials (ASTM):

1.) ASTM F1292-95:

Standard Test Method for Impact Attenuation of Surface Systems Under and Around Playground Equipment.

2.) ASTM F355-95:

Standard Test Method for Shock-Absorbing Properties of Playing Surface Systems and Materials.

3.) ASTM C67:

Standard Test Method for Weathering and Aging of Surface Systems and Materials.

- 4.) ASTM D573:
Standard Test Method for Rubber – Deterioration in an Air Over.
- 5.) ASTM E108:
Standard Test Methods for Fire Tests of Roof Covering Materials.
- 6.) ASTM E108 - Modified:
Modified Test Methods for Fire Tests of Surface Systems and Materials.
- 7.) ASTM E303-93:
Standard Test Method for Measuring Surface Frictional Properties Using the British Pendulum Tester.
- 8.) ASTM F1951-99:
Standard Specification for Determination of Accessibility of Surface Systems Under and Around Playground Equipment.
- 9.) ASTM C518-98:
Standard Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus.

B.) LEED – USGBC:

- 1.) Standards specified under the LEED (Leadership in Energy and Environmental Design) criteria development by the USGBC (United States Green Build Council).
 - a.) Materials and Resources:
Up to 6 points and credits toward LEED certification.
 - b.) Indoor Environmental Quality:
Up to 1 point and credit toward LEED certification.

1.03 SYSTEM DESCRIPTION

A.) Results:

- 1.) Shock Attenuation (ASTM F1292 & F355.95):
 - a. G-max – Less than 200 =PASSED.
 - b. Head Injury Criteria – Less then 1000 =PASSED.
- 2.) Weathering/Aging (ASTM C67, D573 & F1292-95): =.....PASSED.
- 3.) Flammability (ASTM E108 & E108 Modified): =PASSED.
- 4.) Skid Resistance (ASTM E303-93):
 - a. WET =PASSED.
 - b. DRY =PASSED.
- 5.) ADA Accessibility (ASTM F1292-99): =PASSED.

6.) R-Value, Thermal Conductivity (ASTM C518-98): =PASSED.

1.04 SUBMITTALS

A.) General:

Submit listed submittals in accordance with Conditions of the Contract and Division 1 Submittal Procedures Section.

B.) Product Data:

Submit manufacturer's product data, specifications and installation instructions.

C.) Verification Samples:

Submit manufacturer's standard verification samples of 4"X4" minimum. Two of the submitted samples must show the male/female interlocking mechanism and connection.

D.) Quality Assurance/Control Submittals: Submit the following:

1.) Certificate of qualifications of the surfacing installer.

E.) Closeout Submittals: Submit the following:

1.) Warranty documents specified herein.

1.05 QUALITY ASSURANCE

A.) Qualifications:

Utilize an installer having experience with projects of similar scope and complexity.

1.06 DELIVERY, STORAGE & HANDLING

A.) General

Comply with Division 1 Product Requirement Section.

B.) Delivery:

Deliver materials in the manufacturers original, unopened, undamaged containers with identification labels showing and intact.

C.) Storage and Protection:

Store materials protected from exposure to harmful environmental conditions and at a minimum temperature of 30 degrees F and a maximum temperature of 120 degrees F.

1.07 PROJECT/SITE CONDITIONS

A.) Environmental Requirements:

Install surfacing system when minimum ambient temperature is 40 degrees F and a maximum ambient temperature is 90 degrees F. Do not install in steady of heavy rain, snow and/or sleet.

1.08 WARRANTY

A.) Project Warranty:

Refer to conditions of the contract for project warranty provisions.

B.) Manufacturer’s Warranty:

Submit, for Owner’s acceptance, manufacturer’s standard warranty document executed by authorized company official. Manufacturer’s warranty is in addition to, and not a limitation of, other rights Owner may have under contract documents.

1.) Warranty Period:

5 years from date of product shipment. Extended warranties are available upon written request.

PART TWO (2) PRODUCTS

2.01 RUBBERIZED SAFETY SURFACING, FLOORING AND PAVER PRODUCTS IN THE TILE/MAT/BLOCK FORM.

A.) Manufacturer:

Unity Creations, LTD.

Sales & Marketing:

Unity Creations, LTD.

1.) Contact:

3997 RT 9W (PO Box 9)

Saugerties, NY. 12477

T: (845) 246-2700

F: (845) 246-1700

E-mail: Techinfo@surfacingystems.com

Internet: www.surfacingystems.com

3997 RT 9W (PO Box 9)

Saugerties, NY. 12477

T: (845) 246-2700

F: (845) 246-1700

E: productinfo@surfacingystems.com

Internet: www.surfacingystems.com

B.) Proprietary Products/Systems. Rubberized safety surfacing flooring and paver products in the tile/mat/block form, including the following:

1.) Rubberized safety surfacing, flooring and pavers, in the tile/mat/block form:

a.) Materials:

Pigmented tiles/mats/blocks: 100% post-consumer recycled SBR (Styrene Butadiene Rubber) and pigmented polyurethane] [EPDM tiles: post-consumer recycled SBR, recycled post-industrial EPDM (Ethylene Propylene Diene Monomer) rubber and polyurethane].

b.) Thickness and Weight:

- 1” thick is~ 30 lbs. each.
- 1 ¼” (1.75”) thick.....~ 36 lbs. each.
- 2 ¼” (2.25”) thick.....~ 41 lbs. each.
- 3” thick.....~ 47 lbs. each.
- 3 ¼” (3.25”) thick.....~ 50 lbs. each.
- 3 ½” (3.5”) thick.....~ 54 lbs. each.

Note: Custom thicknesses and weights are available prior to specifying and/or orders.

c.) Color:

1.) Pigmented Color:

Black, Splash (Black tile with 50% EPDM granules), Steel Gray, Red (Terra Cotta), Green, Blue, Tan, White, Purple, Teal, Brown.

Note: Other custom colors are available upon request.

2.) EPDM Colors:

Dark Green, Green, Blue, Purple, Yellow, Coca, Charcoal, Lt. Gray, Beige, Eggshell, Red (Terra Cotta), Teal, Dark Blue, Lt. Blue, Hbart Green, Brt. Red, Orange, Mid-Gray, Virgin Black, Dark Brown, Mid-Brown, Gold, Ivory, White.

2.02 PRODUCT SUBSTITUTIONS

A.) Substitutions:

No substitutions permitted.

2.03 ACCESSORIES

A.) Provide accessory items as follows:

- 1.) Unity's Chemrex 948 Urethane Adhesive.
- 2.) Unity's Transitional Ramp, Standard Beveled Edge.
- 3.) Unity's Anchor Bolts.
- 4.) Unity's Geotextile Fabric, Landscaping Mesh.

PART THREE (3) EXECUTION

3.01 MANUFACTURER'S INSTRUCTIONS

A.) Comply with the instructions and recommendations of the rubberized safety surfacing, flooring and paver manufacturer.

3.02 EXAMINATION

A.) Site Verification of Conditions: Verify that substrate conditions are suitable for installation of the rubberized safety surfacing, flooring and paver system.

B.) Do not proceed with installation until unsuitable conditions are corrected.

3.03 PREPARATION

A.) Surface Preparation:

Ensure that the concrete or asphalt substrate is level or uniformly sloped since surface variations will be telegraphed through to the rubber tile/mat/block surface.

3.04 INSTALLATION

A.) Do not proceed with surfacing, flooring and/or paver installation until all applicable site work, including substrate preparation, fencing, playground equipment installation, roofing and other relevant work, has been completed.

B.) Tiles/mats/blocks shall be produced on a rectangular configuration of 22" (inches) by 44" (inches) in size with a shadow-center (fake seam) joint to achieve the use of the "step-&-repeat" systems to stagger the seams as if you were installing brickwork (zigzag). As a result, symmetry of 22" by 22" squares will be seen on properly completed jobs (installations). Each tile/mat/block is 6.72 square feet in size and has a coned (feet or leg) bottom design at 1 ¾" (1.75") thick, 2 ¼" (2.25") thick, 3" thick, 3 ¼" (3.25") thick, 3 ½" (3.5") thick for the "Pave-Land", "Play-Land" and "Soft-Land" series. Avoid placement when large temperature swings during the time between adhesive application and final curing are expected, as gapping between tiles may result.

Note: 1" thick tiles/mats/blocks do not have interlocking system, nor do they have coned (feet or leg) bottoms. Unity's 1" thick material is a solid top and bottom tile/mat/block.

1.) Apply adhesive on tight asphalt (blacktop) or concrete (cement) at a rate of approximately 25 square feet per 825 ml tube. Adhesive consumption will increase as asphalt porosity increases.

2.) Apply adhesive to the base using a large corking-gun.

Note: When one (1) and five (5) gallon pails are used, apply adhesive to the base using a notched trowel.

3.) Apply adhesive to the interlocks, both in the joint and on top of the joint for added strength and security using a corking-gun. Coverage rate is approximately 25 sq. ft. per each 825 ml tube. Such application will allow for proper rainwater drainage.

4.) Maintain a straight line at the tile joints. To keep lines straight, adjust tiles using a rubber mallet as they are installed. Apply a string line on the first couple of rows installed to maintain a straight line of installation.

3.05 PROTECTION

A.) Protect the installed rubberized safety surfacing, flooring and paver products from damage resulting from subsequent construction activity on the site. Do not walk on materials for at least 24 hours after installation to insure proper glue drying and settlement of the installed product.

B.) Prior to application of the rubberized safety surfacing, flooring and paver materials, the installer shall evaluate the substrate's structural performance. Notify all contractors, architects and engineers of all displacements. Work shall not proceed until unsatisfactory conditions are corrected and signed by the contractors, architects and engineers, and installation manual / guide as been read.

PART FOUR (4) SPECIFIER NOTES:

4.01 DISCLOSURES:

A.) Specifier Disclosure Notes:

1.) Revise paragraphs above to suit project requirements. If a reader of this specification could reasonably expect to find a product or component specified in this specification, but it is actually specified elsewhere, then the related section number(s) should be listed in the paragraphs above. In the absence of related sections, delete pertaining paragraph above.

2.) Site materials and methods, drainage, playground equipment, fencing, substrate preparation, roofing materials and similar work are provided by others and are described in other sections. Consult manufacturer for specific substrate preparation requirements. Edit, retain or delete paragraphs above to suit project requirements and specifier practice.

3.) Article above may be omitted when specifying manufacturer's proprietary products and recommended installation. Retain References Article when specifying products and installation by an industry reference standard. If retained, list standard(s) referenced in the above section. Indicate issuing authority name, acronym, standard designation and title. Establish policy for indicating edition date of standard referenced. Conditions of the Contract or Division 1 References Section may establish the edition date of standards. This article does not require compliance with standard. It is a listing of all references used in the pertaining section.

4.) Article above should be restricted to statements describing design or performance requirements and functional (not dimensional) tolerances of a complete system. Limit descriptions to composite and operational properties required to link components of a system together and to interface with other systems.

5.) Article Above includes submittal of relevant data to be furnished by Contractor before, during or after construction. Coordinate the above article with Architect's and Contractor's duties and responsibilities in Conditions of the Contract and Division 1 Submittal Procedures Section.

6.) Article above should include statements of prerequisites, standards, limitations and criteria that establish an overall level of quality for products and workmanship for the section. Coordinate article with Division 1 Quality Assurance Section.

7.) Article above should include specific protection and environmental conditions required during storage. Coordinate article above with Division 1 Product Requirements Section.

8.) Article above, state physical or environmental limitations or criteria for installation such as weather, temperature, humidity, ventilation or illumination required for proper installation or application.

9.) Coordinate article above with Conditions of the Contract and with Division 1 Closeout Submittals (Warranty) Section. Use this article to require special or extended warranty or bond covering the work of this section.

10.) Retain article below for proprietary method specification. Add product attributes, performance characteristics, material standards and descriptions as applicable. Use of such phrases as "or equal" or "or approved equal" or similar phrases may cause ambiguity in specifications. Such phrases require verification (procedural, legal and regulatory) and assignment of responsibility for determining "or equal" products.

11.) The type of playground equipment determines the required tile/mat/block thickness. Depending on ASTM F1292 requirements for critical fall height 4', 6', 8', 10' or 12' (foot), select tile thickness from optional thicknesses 1 3/4" (1.75") thick, 2 1/4" (2.25") thick, 3" thick, 3 1/4" (3.25") thick, 3 1/2" (3.5"), respectively. Specify project requirements above and coordinate with working drawings.

12.) Edit Article above to suit project requirements. If substitutions are permitted, edit text above accordingly. Add text to refer to Division 1 Project Requirements (Product Substitutions Procedures) Section. Specify subordinate or secondary items that aid and assist primary products specified above or are necessary for preparation or installation of those items. Specify actions to physically determine that conditions are acceptable to receive primary products of the section.

13.) Specify actions required to physically prepare the surface, area or site or to incorporate the primary products of the section. Coordinate article above with manufacturer's recommended installation requirements. Specify provisions for protecting work after installation but prior to acceptance by the owner. Coordinate article below with Division 1 Execution Requirements Section.

[Click here](#) for a printable version of this page.